



## Blue Grease HT™ Multipurpose, Water-Resistant, Calcium Sulfonate Complex, High-Temperature Grease



General industrial grease designed for applications involving high heat, water, extreme pressure and high loads. Blue Grease HT™ will not separate, soften or run in applications involving heavy loads.

- NLGI Grade 1-1/2 covers applications requiring a NLGI 1 or 2 grease
- Wide temperature range: 0°F to 554°F (-18°C to +290°C)
- Calcium sulfonate complex base
- Dropping point (ASTM D-2265): 554°F (290°C)
- Water washout (ASTM D-1264): 2.8% loss at 175°F (80°C)
- Four ball wear (ASTM D-2266): 0.45mm scar dia.
- Mobility: 13.6g/minute at 0°F (18°C)
- Timken OK Load (ASTM D-2509): 65 lbs.
- Bearing rust test (ASTM D-1743): Pass
- Resists washout from water or steam
- Applications include outdoor equipment and machinery, bearings, mechanical hoists, water pumps and generators, forklifts, exposed gears and drives, fifth wheel and universal joints



Container Type	Size	Item No.	Pkg. Qty.
Cartridge	14 Oz.	<b>1636081</b>	1
Tub	1 Lb.	<b>1636079</b>	1
Pail	35 Lb.	<b>1636077</b>	35
Drum	120 Lb.	<b>1636078</b>	120
Drum	400 Lb.	<b>1636080<sup>1</sup></b>	400

<sup>1</sup>Usually ships in 2 to 4 days