

Hand Tools

Index-Tend Demo Wrecking Bar

- 27 indexing handle positions and 16 indexing foot positions turns 1 tool into 432 tools (27 x 16 = 432)
- Foot indexes 240° in 20° increments
- Beveled entry tabs on the cleated foot allow for quick entry into tighter spaces
- Heavy-duty solid bar chrome vanadium construction
- Meets and exceeds ANSI requirements
- 19" ergonomically designed handle with 3-1/2" cleated, nail pulling foot



DY89320027

14-in-1 Miniature Ergonomic Precision Dual Head Screwdriver and Torx Driver Set

- Heavy-duty chrome-vanadium molybdenum steel
- 14 tools-in-one
- Compact, light, and convenient enough to carry in a tool pouch



DY81100450

Miniature Screwdrivers Set

- Shafts are made of hardened tool steel and the handle is a shock proof TPR material
- Tips of the screwdriver handles rotate to allow fingertip turning of the screwdriver and reduces hand fatigue



DY81100091

Fluid Power Tools

Safety High Flow Blowguns

Our most powerful blowguns. Use to blow off even the heaviest shavings and chips. Delivers 35 CFM with a high flow tip and 51 CFM with a multi-jet tip. Each of these are lightweight and ergonomic, and features a variable flow trigger for optimum control and ease of use.

- Chrome-plated to resist chemicals and solvents
- Meets or exceeds OSHA regulations

29612 - 1/4" NPT Blowgun with High Flow Tip

29613 - 3/8" NPT Blowgun with Multi-Jet Tip and High Flow Tip



29612



29613

Cutting Tools

Falcon Tools® Jobber Length Drill Bit Sets

- 135° split point
- Self-centering point eliminates drill walking
- Manufactured from top-quality steel to reduce breakage and increased toughness and longer tool life
- 1/16" to 1/2" by 64ths
- 29 pc. set



FA4037

FA4038

FA4037
FA4038

Masonry Drill Bit Set

- Carbide tip
- Wide spiral
- Meets ANSI B94.12 Standards
- For rotary drills

93936 - 7 Pc. Set, 1/8" to 1/2" Standard Length



E3884

V1 (12/23)



Electrical

Wire Lever-Nut Connector

- Works with either solid or stranded wire from 28 to 12 AWG
- Works with combinations of wire sizes and types in one connector
- Touch-safe with integrated built-in test point
- Small and compact
- 25 Pkg. Qty.

DY20733002 - 2 Wire

DY20733003 - 3 Wire

DY20733005 - 5 Wire



Push and Lock Wire Connectors

- Easy-to-use connector for making wire splices
- Each wire is individually locked in the connector
- See-through housing allows easy visual installation – wire locks easily into terminal
- UL/ULC listed for solid wire
- 50 Pkg. Qty.

64655 - 2 Wire, Red
64657 - 4 Wire, Yellow
64658 - 5 Wire, Gray



Material Handling

Urethane Rope and Hooks

- Make your own shock cords – simply cut a length of rope to 2/3 of your needed stretch length and attach the nylon/fiberglass hooks
- Product requires more effort to stretch at colder temperatures but remains elastic down to -40°F (-40°C). The product will have very little memory below -10°F (-23°C) but will return when warmed

99973 - 1 Pkg. Qty. - Rope - 5/16" x 125'

99974 - 2 Pkg. Qty. - Rope Hooks



Urethane Tarp Straps

- Come with galvanized steel hooks
- Maximum safe working stretch range is twice the at-ease length

95778 - 12" Length

95779 - 18" Length

95780 - 24" Length

97433 - 31" Length



Shock Cords

- Nylon/fiberglass hooks molded directly into the cord

95775 - 12" Long

95776 - 18" Long

95777 - 24" Long

