



Patented Comfort Grip Trigger Release

Spring Closing Lid With Neoprene Gasket Vents at 5 PSI Internal Pressure

Fixed Handle

Non-Sparking Flame Arrestor and Pour Spout

Baked On Powder Coat Finish

Available in 1, 2 and 5 Gallon Sizes

Double Interlock No-Weld Bottom Seam

Meets OSHA and NFPA Code 30 Requirements, FM, UL and ULC Approved

Lead-Free Technology Featuring Environmentally Friendly Hot Dipped 24 Ga. Galvanized Steel

Optional F-15 HDPE Funnel Fits Unleaded Fuel Tanks

The Only Deep Drawn Seamless Can Made
Deep Drawn Construction Means No Top or Side Seam

Trilingual Label

100% Leak Tested

EAGLE SAFETY

MANUFACTURING COMPANY
WELLSBURG, W. VA. 26070
UI-50-FS TYPE I
Capacity: 5 U.S. Gal.,
4 Imp. Gal., - 18.9 Liters
Write Eagle for replacement parts
U.S. PAT. 4,491,281

DANGER
EXTREMELY FLAMMABLE-VAPORS CAN BE
HARMFUL OR FATAL IF SWALLOWED
IF SWALLOWED, DO NOT INDUCE VOMITING. CALL
KEEP OUT OF REACH OF CHILDREN. KEEP
AVOID PROLONGED BREATHING OF VAPORS.
DO NOT STORE IN VEHICLE OR ANY OTHER
VAPORS CAN BE IGNITED BY A SPARK OR FLAME.
KEEP AWAY FROM FLAMES, HOT SURFACES,
OTHER SOURCES OF IGNITION. KEEP CONTAINER

KEEP AWAY FROM HEAT
BEFORE REWINDING - OPERATE WITH
KEEP CHILDREN AWAY FROM
POUR CAREFULLY TO PREVENT
SPILLS

PAT. PEND.
KEEP OUT OF REACH OF CHILDREN

UI-50-FS 12-1/2" x 13-1/2"