

MOLY CHAIN LUBRICANT




LUTM202



For use in extreme pressure applications



NSF® Registered; H2 Rated (Lubricants with no contact) (Registration # 115087)



Minimum - Maximum operational temperature range: Low -20 °F (-29 °C) • High 300 °F (149 °C)



Features Spray Anyway™ nozzle



HMS Hazard Rating: Health (2) • Flammability (4) • Reactivity (0)

- Works under extreme pressure
- Penetrating foaming action
- Moly additive improves load ability



PRESERVE. PROTECT. PREVENT.™

Sprayon® LUTM202 Moly Chain Lubricant is a high viscosity oil that clings to moving parts. Foaming action penetrates close tolerances of chain drive bushings and pins to provide long-lasting lubrication. Reduces friction wear on moving parts and in metal-to-metal applications. The 'moly' additive improves its capacity to handle greater pressure requirements of start-up stress. SPRAY ANYWAY™ Valve allows material to be applied to the surface when the can is being held in either upright or inverted position.

LUBRICANTS

USES

- Chain drives and pins
- Forklift trucks
- Link and roller assemblies
- Machinery
- Work-stand rollers
- Assembly lines
- Packaging equipment
- Motorcycle and bicycle chains
- Sprockets
- Clippers
- Cutter bars
- Chain saws
- Bushings
- Hoist chains
- Conveyors
- Tractors



LU202

APPLICATION

Maximum performance is achieved when the metal surfaces to be protected are clean, dry and free of rust, oil and mill scale. Product should be sprayed in a well ventilated area. Sprays best at room temperature (70 F.) Shake well before using. Spray at a distance of 10' to 12' from surface.

PERFORMANCE

PLASTIC SAFE: Yes

TEMPERATURE RANGE:

LOW: -20°F

HIGH: 300°F

LOAD CAPACITY: Extreme Pressure

- NSF Registration Number 115087; H2 Rated
- Penetrant
- Water-Displacer
- Rust Inhibitor
- Reduces friction wear on moving parts
- Lubricates between close tolerances
- Provides a penetrating 'foaming' action
- Lubricating film is long-lasting and non-drying
- Equipped with SPRAY ANYWAY™ valve and extension tube

PACKAGING

Stock #: S00202

UPC Code: 0-75577-90202-6

Fill Wt.: 11 oz.

Per Case: 12

Carton Dimensions:

L 10-7/8" x W 8-3/16" x H 8"

PROPERTIES

APPEARANCE: Light Amber

ODOR: Mild Solvent

PROPELLANT: Hydrocarbon

WT./GAL.: 6.34

SPECIFIC GRAVITY: 0.76

PAINTABLE: No

% VOC AEROSOL: 31.80%

V.O.C. COMPLIANT CALIFORNIA: Yes

V.O.C. COMPLIANT OTC STATES: Yes

FLAMMABLE: Yes

FLASH POINT: <0°F

HAZARD RATING: 2,4,0

SHELF LIFE: 3 years from date of manufacture

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.

RESOURCES

MSDS/EDS/PRODUCT DATA SHEETS:

sprayon.com

CUSTOMER SERVICE:

1-800-777-2966

TECHNICAL INFORMATION:

1-800-251-2486



© 2010 Sprayon® Products Made in U.S.A.

Distributed by:

Lawson Products, Inc.

To order these and other products, contact us:

866-529-7664 lawsonproducts.com

PRESERVE. PROTECT. PREVENT.



Sprayon® Products

101 Prospect Ave. NW

Cleveland, OH 44115

Sprayon.com

1-800-777-2966

310-PDS-LU202