

_	_	_
W	NAL NAL	- L <i>OP</i> 1
	CAUTIO	A CHICAGO

Overview

Breaks down grease and oil to clean surfaces without leaving a residue. Whallop cleans surfaces fast and powers through heavy soil layers to lift oil and grease from the surface. Spray Whallop on dirty surfaces and wipe away clean without any heavy scrubbing.

Features/Benefits	 Safe and effective cleaning and degreasing Safe on ferrous and non-ferrous metals Safe on rubber and elastomers Safe on Lexan[®] and Plexiglas[®] Cuts through grease and grime Lexan[®] is a registered trademark of GE Plastic Corp. Plexiglas[®] is a registered trademark of Arkema Inc. 	 Long-lasting clinging foam Easy-rinse formula No ammonia Safe for filmed surfaces
Applications	 Air filters Air conditioner covers Oil and antifreeze spot cleaning on concrete and brick Chrome Countertops and kitchen appliances 	 Engines Restroom fixtures, sinks and tubs Tile, marble and granite Painted surfaces Vehicle wheels
Method of Application	• Aerosol	
Identification	White clinging foam	
Size	• 20 Oz. Can Size; 18 Oz. (510g) Net Wt.	
(1 of 2)		



Directions for Use

Simply spray, allow a few seconds to penetrate, then wipe. Repeat if necessary for heavy soil, grease or extreme applications

Technical Specifications	Form: Aerosol
-	Color: White
	Odor: Pleasant
	 Specific Gravity (Concentrate): 0.9800 at 70°F (21°C)
	• pH: 12.5
	 Reportable VOC Content: 7.85% by weight
	 Boiling Point (Concentrate): 208.0°F (97.8°C)
	Shelf Life: Minimum one year

• HMIS: H:3 F:4 R:0