PRIZM PENETRATING GEL LUBRICANT with PTFE



PROBLEM SOLVER

PROBLEM:

Many lubricating gels are not effective on moving parts and need to be reapplied often.

- Can't be applied through tight gaps, cracks, and small openings.
- Won't adhere to metal and sling off.
- Leave stains behind.
- Can't withstand extreme temperatures.

SOLUTION:

Drummond[®] Prizm Penetrating Gel Lubricant with PTFE

- Sprays as a fine mist to penetrate gaps and crevices, then sets as a grease-like lubricant.
- Highly adhesive gel resists sling-off, squeeze-out, vibration, impact, and shock.
- Colorless and virtually invisible in use.
- Lubricates at a broad temperature range of -30°F to 530°F (-34°C to 277°C)
- Leaves a protective coating that prevents rust and corrosion.



Scan Code To See it in Action

DRUMMOND®



APPLICATIONS:

- Open gears
- Locks
- Hinges
- Conveyor chains
- Rollers
- Cams
- Slides
- Bearings
- Dollies
- Manifold heat valves
- Piano-type hinges
- Nuts
- Bolts and more

INDUSTRIES:

- Agriculture
- Automotive
- Construction
- Equipment rental
- Facility maintenance
- Government
- Manufacturing all
- Mining
- Transportation
- Utilities

