



Safety Push-Button Couplers

Safely Connect and Release Pneumatic Tools, Blow Guns or Air Hoses with One-Click



Perfect Seal for Unrivaled Performance

- Better sealing, leak-free design cuts energy costs
- Valve seal optimizes flow rate for higher power and efficiency

Easy to Use-Connect & Disconnect Design

- Quicker tool and hose change connections
- One-click push button vents air pressure before disconnecting to prevent whip injury
- Built to comply with ISO 4144 standards

Durable Construction Saves Time & Money

- Made of scratch-resistant composite material to withstand harsh production environments
- Rugged non-brass construction will not harm work finishes
- Longer lasting, 5:1 replacement ratio, against competitive couplers
- Color-coded button for easy identification



Leak Free Connection Design



Impact and Crush Resistance Construction



Eliminates Hose Whip Injuries

Safety Push-Button Couplers

Safety Couplers from Lawson Products ensure a safe workplace and significantly reduce personal injury during disconnection. You can safely connect the coupler in seconds by pushing a single button.

Use the table below to order the one-click safety couplers

Image	New Generation Lawson Number	One Push Safety Description	Profile	Body Size	Thread Size (Inches)
A	1489993	FNPT	Industrial	1/4"	1/4-18
A	1489994	FNPT	Industrial	1/4"	3/8-18
B	1489995	MNPT	Industrial	1/4"	1/4-18
B	1489996	MNPT	Industrial	1/4"	3/8-18
A	1489997	FNPT	Industrial	3/8"	1/4-18
A	1489998	FNPT	Industrial	3/8"	3/8-18
B	1489999	MNPT	Industrial	3/8"	3/8-18
C	1490003	FNPT	Truflate	1/4"	1/4-18
C	1490004	FNPT	Truflate	1/4"	3/8-18
D	1490005	MNPT	Truflate	1/4"	1/4-18
D	1489990	MNPT	Truflate	3/8"	3/8-18
C	1489991	MNPT	Truflate	3/8"	1/4-18
C	1489992	FNPT	Truflate	3/8"	3/8-18
E	1490000	FNPT	ARO 210	1/4"	1/4-18
F	1490002	MNPT	ARO 210	1/4"	1/4-18



BLUE - Industrial Interchange RED - Truflate YELLOW - ARO 210

Complete Your Job with these Helpful Items

Dynaswivel® Air Line Connectors

- Lightweight, resilient, industrial quality connectors swivel 360°
- Two pivot points allowing the air line to drop to the floor, resulting in increased maneuverability



58565

27175

Polyurethane Self-Coiling Air Hose

Thread Connection (NPT) (Inches)	Length (Ft.)	Tube O.D. (Inches)	Tube I.D. (Inches)	Item No.
1/4	5	1/4	0.160	51922
	5	3/8	1/4	51923
	10	1/4	0.160	52134
	15	3/8	1/4	52135
	25	3/8	1/4	52136
	50	1/4	0.160	55535
3/8	50	3/8	1/4	55536
	5	9/16	3/8	98667
	15	9/16	3/8	52137
	25	9/16	3/8	52138
	50	9/16	3/8	98668



Heavy-Duty Quick Disconnect Air Couplers Male NPT Swivel Plug

Standard or Industrial Interchange Design

- Built-in sleeve guard to minimize accidental disconnect
- Ball swivel design to enhance air line flexibility and help prevent repetitive motion injury
- Stainless steel coupling balls and springs for corrosion resistance



27172

64406

Heavy-Duty Quick Disconnect Air Couplers Male NPT Swivel Plug

Tru-Flate Design

- Built-in sleeve guard to minimize accidental disconnect
- Ball swivel design to enhance air line flexibility and help prevent repetitive motion injury
- Stainless steel coupling balls and springs for corrosion resistance
- Maximum working pressure: 300 PSI
- Temperature range: -40°F to +250°F (-40°C to +121°C)



27173

64407

© 2018 Lawson Products, Inc. All rights reserved. Printed in USA.

Ordering Is Easy

On-Site
Your Lawson Representative

Online
lawsonproducts.com

On The Phone
USA: 866.529.7664 Canada: 800.563.1717