

DRY FILM GRAPHITE LUBRICANT



LU™ 204




Medium Pressure Lubricant



NSF® Registered; H2 Rated (Lubricants with no contact) (Registration # 131585)



CONDUCTIVE - DO NOT USE ON ELECTRIC EQUIPMENT



Minimum - Maximum operational temperature range: Low -40 °F (-40 °C) • High 850 °F (454 °C)



HMS Hazard Rating: Health(2) • Flammability (4) • Reactivity (0)

- Works up to 850°F/1000°F intermittently
- Dries rapidly
- Excellent conductivity
- Coefficient of friction, .123



PRESERVE. PROTECT. PREVENT.™

Sprayon® LU™ 204 Dry Film Graphite Lubricant is a high lubricity graphite that adheres to most surfaces with minimum surface preparation. It air dries rapidly at room temperature to provide clean, long-wearing lubrication. This lube is also conductive and may be used where lubrication and electrical properties are both required. Effective in temperature up to 850°F. constant and 1000°F. intermittent. Low friction coefficient (.123) allows parts to move easily.

LUBRICANTS

USES

- Pre-assembly lubrication of moving parts
- Mechanisms of vending machines and parking meters
- Automotive and industrial gaskets
- Bearings • Chains
- Springs • Locks
- Bushings • Gaskets



LU204

APPLICATION

Maximum performance is achieved when the metal surfaces to be protected are clean, dry and free of rust, oil and mill scale. Product should be sprayed in a well ventilated area. Sprays best at room temperature (70F.) Shake well before using. Spray at a distance of 10" to 12" from surface.

PERFORMANCE

PLASTIC SAFE: No

TEMPERATURE RANGE:

LOW: -40°F

HIGH: 850°F constant (1,000°F) intermittent

LOAD CAPACITY: Extreme Pressure

COEFFICIENT OF FRICTION (ASTM D-4518): .123

- NSF Registration Number 131585; H2 Rated
- Penetrant
- Water-Displacer
- Rust Inhibitor

PROPERTIES

APPEARANCE: Black

ODOR: Mild solvent

PROPELLANT: Hydrocarbon

WT./GAL.: 5.23

SPECIFIC GRAVITY: 0.63

PAINTABLE: No

% VOC AEROSOL: 99.05%

V.O.C. COMPLIANT CALIFORNIA: Yes

V.O.C. COMPLIANT OTC STATES: Yes

FLAMMABLE: Yes

FLASH POINT: <0°F

HAZARD RATING: 2,4,0

SHELF LIFE: 3 years from date of manufacture

RESOURCES

MSDS/EDS/PRODUCT DATA SHEETS:

sprayon.com

CUSTOMER SERVICE:

1-800-777-2966

TECHNICAL INFORMATION:

1-800-251-2486

PACKAGING

Stock #: S00204

UPC Code: 0-75577-90204-0

Fill Wt.: 10 oz.

Per Case: 12

Carton Dimensions:

L 11.13" x W 8.44" x H 8.38"

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.



© 2010 Sprayon® Products Made in U.S.A.

Distributed by:

Lawson Products, Inc.

To order these and other products, contact us:

866-529-7664 lawsonproducts.com

PRESERVE. PROTECT. PREVENT.



Sprayon® Products

101 Prospect Ave. NW

Cleveland, OH 44115

Sprayon.com

1-800-777-2966

310-PDS-LU204