



Overview

Prizm is an all-purpose, penetrating gel lubricant. A unique combination of PTFE, natural and synthetic lubricants and a high molecular weight polymer allow Prizm to penetrate, coat and cure to a grease-like gel. Prizm protects against rust and corrosion while reducing heat, friction and wear.

Features/Benefits

- Sprays on as a penetrating foam, then dries to a lubricating film
- Non-sling formulation
- Contains PTFE
- Penetrates and wicks into cavities and tight openings
- Protects against friction and wear
- Reduces metal-to-metal friction and wear
- Protects against rust and corrosion
- Aerosol spray designed to lubricate hard-to-reach areas
- USDA authorized
- CFIA authorized

Applications

- Penetrates and restores movement of metal parts
- Lubricates and protects chains, sprockets, rollers and cutting bars
- Food manufacturing and service locations
- Meat plants
- Poultry and egg plants
- Marine and boat
- Forestry service equipment
- Farm implements
- Equipment with outdoor service
- Construction equipment

Method of Application


- Aerosol

Identification

- Aerosol, penetrating oil

Size

- 20 Fl. Oz. Can Size: 13 Oz. (368g) Net Wt.



Directions for Use

1. Shake aerosol can well.
2. Prizm works best when surfaces to be sprayed are free of debris, dirt and moisture.
3. Spray surfaces generously; saturate area.
4. Wait a few moments for lubricant to penetrate into surface cavities and for solvent to dry.
5. Use extension tube for hard-to-reach areas.
6. Wipe excess from painted surfaces.

Technical Specifications

- Form: Aerosol
- Color: Amber
- Odor: Petroleum/solvent
- Water Solubility: Negligible
- Specific Gravity (Concentrate): 0.736 at 70°F (21°C)
- Evaporation Rate: >1 (butyl acetate = 1)
- Reportable VOC Content: 49.84% by weight
- Shelf Life: Minimum one year
- HMIS: H:1 F:4 pH:1